Material Safety Data Sheet May be used to comply with	U.S. Department of Labor Occupational Safety and Health Administration					
OSHA's Hazard Communication Standard	(Non-Mandatory Form)					
29 CFR 1910.1200. Standard must be	Form Approved					
consulted for specific requirements.  IDENTITY RESIN FIBER DISC		OMB No. 1218-0072 Forms Published by ChemSWM, Inc. (707)864-0846				
IDENTITY RESIN FIBER DISC	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that,					
		TODATION S	available, the space m	GOT DE MAINDA IO MAICA	IG NIAL	
Section I						
Manufacturer's Name	Emergency Telephone Number					
GLIT/GENTEX COMPANY LIMITED	416 245 5605					
Address (Number, Street, City, State, and ZIP Cod	Telephone Number for Information 416 245 5505					
60 BELFIELD ROAD	416 245 5605  Date Prepared					
TORONTO, ONTARIO	3-Jan-01					
TORONTO, CRIMITO	··· ·	Signature of Preparer (optional)				
M9W 1G1, CANADA	The state of the s					
Section II - Hazardous Ingredients/Ide	entity Information	1	CHICKLE .			
Section it - Hazardous ingredientshire	stitity information	1		Other Limits		
Hazardous Components (Specific Chemical Identity	OSHA PEL	ACGIH TLV	Recommended	% (optional)		
VULCANIZED FIBER		N/A	N/A	N/A	30-70	
ALUMINUM OXIDE Al2o3		15 mg/m3	10 mg/m3	1344-28-1	5.0-50	
ZIRCONIA ALUMINA ZrOZ		5 mg/m3	5 mg/m3	1314-23-4	00-30	
BINDER SYSTEM	W 1 - 1 M	N/A	N/A	N/A	13-25	
CRYOLITE Na3Alf6	15 mg/m3	2 mg/m3	15096-523	6.0-15		
Section III - Physical/Chemical Charac	cteristics					
Boiling Point		Specific Gravity (F	120 = 1)		N/A	
	N/A	Melting Point		1.0	N/A	
Vapor Pressure (mm Hg)	N/A	Melmin Louir			N/A	
Vapor Density (AIR = 1)		Evaporation rate	ATT TO THE TOTAL TOTAL TO THE THE TOTAL TOTAL TO THE TOTAL TO THE TOTAL TO THE TOTAL TO THE TOTA			
	N/A	(Butyl Acetate = 1)			N/A	
Solubility in Water						
N/A						
Appearance and Odor						
Green backing-odorless						
Section IV - Fire and Explosion Hazar	d Data					
Flash Point (Method Used)		Flammable Limits		LEL .	0EL	
N/A		A	N/A	N/A		
Extinguishing Media			i maniahina a			
Water spray, Co2, Foam, Dry che	emical or any	Class A ext.	ruduranınd ad	) GII +		
Special Firefighting Procedures  Backing & resin binder will but	rn or decompos	e. Use respi	iratory prote	ection.		
backing & restn pringer wiff but	TI OT GECOMPOS	~- 554 745E-		Later 1		
Unusual Fire and Explosion Hazards N/A	and Me	A Library (70):				

Section V -	Reactivity Da	ita					
Stability	Unstable	T	Conditions to Avoid				
	Stable				LAWRITT		
		X	No applicable inform	mation found			
Incompatibility (I	viaterials to Avoid	)					
Hamidana Dago	mposition or Byp	roduci	is .	7.5	- Land Taring Land		
	e, dust and	l tu	mes are generated, go Conditions to Avoid	merally more iro	m material being ground.		
Hazardous Polymerization	May Occur	1	Caliditions to Avoid				
	Will Not Occur	x	No applicable inform				
Section VI -	Health Hazai		AND DESCRIPTION OF THE PERSON	DOK DEPORT DESCRIPTION			
Houte(s) of Entry			Inhalation?	Skin?	Ingestion? Not known nor recommends		
Health Hazards	Acute and Chron	c) rab	fume/dust during use le - 5mg/m3, total -		itate eyes, elevated sound		
				NAME .			
level duri	ng use on	SOM	e metal / jobs.		AND THE RESERVE OF THE PERSON		
	- Asomo		NTP?	ARC Monographs?	OSHA Regulated?		
Carcinogenicity:			N/A	N/A	N/A		
Signs and Symp	oms of Exposure				- officet broothing may cauco		
				aue to dust, ma	y affect breathing, may cause		
		st Y	may irritate eyes.	War Harmon La	A LANGE OF THE STATE OF THE STA		
Medical Condition Generally Aggray	ns rated by Exposure		N/A				
				1	<del>-</del> "		
Emergency and	First Aid Procedu	ne		1	single of a modical accident		
Remove to	fresh air	if :	needed, wash eyes wit	h water, optain	First aid or medical assistant		
	necessary.		A. C.	U. S. C.			
Section VII -	Precautions	for	Safe Handling and Use	***			
N/A	n in Case Materia	II IA FIL	steased of Opinion	,			
<del></del>							
Waste Disposal	Method				- Jah amalianahla Endowal etata		
No special	procedure	rec	mired, standard land	till consistance	with applicable federal, state		
and local	laws.						
Precautions to be	Taken in Handlir OSHA 29cC	ng and FR I	Storage  910-94 (ventilation)	and OSHA 29C FR	1910.1000 (air contaminates)		
					- 70 deg. F with ventilation.		
Other Precautions Use CAMI (Coated Abrasive Mfg. Institute) guidelines, follow tool guidelines.							
				A STATE OF THE STA	ALL THE THE TAXABLE PARTY.		
Section VIII -	Control Mea	sur	9S	The state of the s			
Respiratory Prote	ction (Specity Ly) d → approv	pe} e d∖	ist respirator OSHA 2	4C FR 1910.134			
Ventilation	Local Exhaust			Ispecial	Special No applicable information found		
	Recommende Mechanical (Gen			Other			
Protective Glove	Recommende	d		No applicable in	TOTAL CTOU		
Recommende	đ		27.77		LANCE CONTRACTOR OF THE PARTY O		
Other Protective	Clothing or Equip	ment	ommended to cover exp	osed skin			
					24 A 25 A A 26 A 26 A 26 A 26 A 26 A 26 A		
Work/Hygenic Practices Eye/face/hearing protection - (ANSI std. Z87.1) OSHA 29CFR 1910.133 , OSHA 29CFR 1910.134							